

# RAISE BORE DIVISION SBM 450

FAST.
EFFICIENT.
RESPONSIVE.

#### 1000V HYDRAULIC DRIVE MACHINE

The SBM 450 is a compact, dual-purpose rig specifically designed for conventional rises and boxhole slot rises while maintaining a low profile. It is a complete system for drilling long holes and boring raises as large as 2.4m in diameter and up to 350m in length.

#### **FEATURES**

- Capable of reaming 700mm to 1.1m diameter up-hole slots up to 60m in length and conventional rises up to 2.4m in diameter and up to 350m in length
- Mechanised wrenching system and lay-down rod handler
- Hydraulic drive system to improve transfer of energy and reduce power consumption

#### INTEGRATED UNDERGROUND MINING SERVICES:

- Mine development
- Production mining
- Cable bolting, production drilling and ITH drilling
- Raise boring and specialist boxhole boring
- Shotcreting
- Plant and equipment hire



## SBM 450

### 1000V Hydraulic Drive Machine

OPERATIONAL		
Up-hole Slot Diameter	Diameter Length	700mm to 1.1m 60m
Conventional Ream Diameter	Diameter Length	1.1m to 2.4m 350m
Raise Angle	Up-hole Slot Mode Ream Mode	60 degrees to vertical 45 degrees to vertical
Pilot Hole Diameter	Normal Maximum	11" (297mm) 12-1/4" (312mm)

TECHNICAL		
Rotation System	Туре	Hydraulic Drive
Pilot Drilling Data	Pilot RPM Pilot Thrust	0 – 60RPM variable 470kN (106,000 lbs)
Reaming Data	Reaming RPM Reaming Thrust Reaming Torque Maximum Torque	0 – 16RPM variable 1,700kN (384,000lbs) 76kNm (56,000ft/lbs) 108kNm (80,000ft/lbs)
Drill Pipe Data	Diameter Length s/s	HS 10" (254mm) 1.525m

ELECTRICAL		
Power Supply	Main Supply Generator Transformer Supply Cable Size	1000V, 50hz 300Kva 250Kva 32mm <sup>2</sup>
Power Pack Supply	Power Rating Full Load Current Starter Type Start Up Current Voltage	150Kw (200Hp) 108A Soft Starter 260A 1000V

CONSUMPTION		
Air	Pilot Drilling Air	17m³/min @ 7 bar (400cfm @ approximately 100psi)
Water		Approximately 500 litres/min which is recirculated
		via sumps Approximately 75 litres/min

WATER PUMP		
Water Recycling	Pilot Drilling Water	37kW (pending pilot hole diameter and length)

RAISE BORE RIG		
Dimensions	Weight	4.100m 4.100m 1.950m 2.100m 12.2 tons 4.0m x 400mm high beams
Transporter	Diesel Crawler	With inbuilt erection device



